

Reifengrösse			Rad-Durchmesser (mm)	Abrollumfang (mm)	Empfohlene Felgenbreite (Zoll)	Zulaessige Felgenbreiten (Zoll)
Breite (mm)	Querschnitt (%)	Felgendurchmesser (Zoll)				
165	65	13	545	1661	5	4.5 – 6
175	65	13	558	1701	5	5 – 6
175	60	13	540	1648	5	5 – 6
185	60	13	552	1684	5.5	5 – 6.5
205	60	13	576	1757	6	5.5 – 7.5
195	55	13	545	1661	6	5.5 – 7
175	50	13	505	1541	5.5	5 – 6
205	50	13	535	1632	6.5	5.5 – 7.5
215	50	13	545	1663	7	5.5 – 8.5
195	45	13	506	1542	6.5	6 – 7.5
225	45	13	533	1625	7.5	7 – 8.5

165	65	14	570	1739	5	4.5 – 6
175	65	14	583	1778	5	5 – 6
185	65	14	596	1818	5.5	5 – 6.5
195	65	14	609	1858	6	5.5 – 7
175	60	14	566	1725	6	5 – 6
185	60	14	578	1762	5.5	5 – 6.5
195	60	14	590	1798	6	5.5 – 7
185	55	14	559	1705	6	5 – 6.5
185	50	14	541	1649	6	5 – 6.5
195	45	14	531	1620	6.5	6 – 7.5
205	45	14	540	1647	7	6.5 – 7.5
225	40	14	536	1634	8	7.5 – 9
255	35	14	534	1629	9	8.5 – 10

185	65	15	622	1896	5.5	5 – 6.5
195	65	15	635	1935	6	5.5 – 7
205	65	15	648	1975	6	5.5 – 7.5
215	65	15	661	2015	6.5	6 – 7.5
185	60	15	603	1839	5.5	5 – 6.5
195	60	15	615	1876	6	5.5 – 7
205	60	15	627	1912	6	5.5 – 7.5
225	60	15	651	1986	6.5	6 – 8
185	55	15	585	1783	6	5 – 6.5
195	55	15	596	1816	6	5.5 – 7
205	55	15	607	1850	6.5	5.5 – 7.5
235	55	15	640	1950	???	6.5 – 8.5
195	50	15	576	1757	6	5.5 – 7
205	50	15	586	1787	6.5	5.5 – 7.5
225	50	15	606	1848	7	6 – 8
195	45	15	557	1697	6.5	6 – 7.5
205	45	15	566	1725	7	6.5 – 7.5
215	45	15	575	1752	7	7 – 8
215	40	15	553	1687	7.5	7 – 8.5
285	40	15	609	1857	10	9.5 – 11
245	35	15	553	1685	8.5	8 – 9.5

205	55	16	632	1927	6.5	5.5 – 7.5
215	55	16	643	1961	7	6 – 7.5
225	55	16	654	1994	7	6 – 8

Reifengrösse			Rad-Durchmesser (mm)	Abrollumfang (mm)	Empfohlene Felgenbreite (Zoll)	Zulaessige Felgenbreiten (Zoll)
Breite (mm)	Querschnitt (%)	Felgendurchmesser (Zoll)				
195	50	16	601	1834	6	5.5 – 7
205	50	16	611	1865	6.5	5.5 – 7.5
225	50	16	631	1926	7	6 – 8
235	50	16	641	1956	???	6.5 – 8.5
195	45	16	582	1775	6.5	6 – 7.5
205	45	16	591	1802	7	6.5 – 7.5
215	45	16	600	1830	7	7 – 8
225	45	16	609	1857	7.5	7 – 8.5
245	45	16	627	1912	8	7.5 – 9
195	40	16	562	1715	7	6.5 – 7.5
215	40	16	578	1764	7.5	7 – 8.5
225	40	16	586	1789	8	7.5 – 9
215	35	16	557	1699	7.5	7 – 8.5
255	35	16	585	1784	9	8.5 – 10

205	55	17	657	2005	6.5	5.5 – 7.5
205	50	17	637	1942	6.5	5.5 – 7.5
215	50	17	647	1973	7	6 – 7.5
225	50	17	657	2003	7	6 – 8
205	45	17	616	1880	7	6.5 – 7.5
215	45	17	625	1907	7	7 – 8
225	45	17	634	1935	7.5	7 – 8.5
235	45	17	643	1962	8	7.5 – 9
245	45	17	652	1990	8	7.5 – 9
195	40	17	588	1793	7	6.5 – 7.5
205	40	17	596	1817	7.5	7 – 8
215	40	17	604	1842	7.5	7 – 8.5
235	40	17	620	1890	8.5	8 – 9.5
245	40	17	628	1915	8.5	8 – 9.5
255	40	17	636	1939	9	8.5 – 10
265	40	17	644	1964	???	9 – 10.5
275	40	17	652	1988	???	9 – 11
215	35	17	582	1776	7.5	7 – 8.5
225	35	17	589	1797	8	7.5 – 9
245	35	17	603	1840	8.5	8 – 9.5

215	45	18	651	1985	7	7 – 8
225	45	18	660	2012	7.5	7 – 8.5
245	45	18	678	2067	8	7.5 – 9
205	40	18	621	1895	7.5	7 – 8
215	40	18	629	1919	7.5	7 – 8.5
225	40	18	637	1943	8	7.5 – 9
235	40	18	645	1968	8.5	8 – 9.5
245	40	18	653	1992	8.5	8 – 9.5
255	40	18	661	2017	9	8.5 – 10
215	35	18	608	1853	7.5	7 – 8.5
225	35	18	615	1875	8	7.5 – 9
235	35	18	622	1896	8.5	8 – 9.5
245	35	18	629	1918	8.5	8 – 9.5
255	35	18	636	1939	9	8.5 – 10
265	35	18	643	1960	9.5	9.5 – 10.5

Reifengröße			Rad-Durchmesser (mm)	Abrollumfang (mm)	Empfohlene Felgenbreite (Zoll)	Zulaessige Felgenbreiten (Zoll)
Breite (mm)	Quer-schnitt (%)	Felgen-durchmesser (Zoll)				
225	40	19	663	2021	8	7.5 – 9
245	40	19	679	2070	8.5	8 – 9.5
215	35	19	633	1931	7.5	7 – 8.5
225	35	19	640	1952	8	7.5 – 9
235	35	19	647	1974	8.5	8 – 9.5
245	35	19	654	1995	8.5	8 – 9.5
255	35	19	661	2016	9	8.5 – 10
265	35	19	668	2038	9.5	9.5 – 10.5